


EXTERIOR ELEVATION UNIT

NOT TO SCALE




PLAN VIEW

NOT TO SCALE


UNIT INFORMATION
FRAMING TYPE: G1 International Hopper Window with Insulbar Thermal Break
GLAZING SET UP: Opening for 1" to 1 $\frac{3}{8}$ " Insulated Glazing, Polycarbonate, or Solid Panel Infill
Decorative interior and exterior grid option.
Motorized Panels Possible
Minimum Vertical Dimension 22". Smaller Dimension may be available upon Engineering Approval
Maximum Sash Weight 200lbs. Larger Sash Weight may be available upon Engineering Approval
Designed and Manufactured in the U.S.A.

~ SOLAR INNOVATIONS' GEN. 1 INTERNATIONAL HOPPER WINDOW ~

© 2017 Solar Innovations, Inc. - All Rights Reserved. These plans are the property of Solar Innovations, Inc. Any use or reproduction of these plans, in whole or in part, without the written permission of Solar Innovations, Inc. is forbidden.



© 2017 Solar Innovations, Inc. - All Rights Reserved. These plans are the property of Solar Innovations, Inc. Any use or reproduction of these plans, in whole or in part, without the written permission of Solar Innovations, Inc. is forbidden.



© 2017 Solar Innovations, Inc. - All Rights Reserved. These plans are the property of Solar Innovations, Inc. Any use or reproduction of these plans, in whole or in part, without the written permission of Solar Innovations, Inc. is forbidden.