



EXTERIOR ELEVATION

~ SOLAR INNOVATIONS' MULTI-TRACK SLIDER ~



PLAN VIEW - PANELS CLOSED



PLAN VIEW - PANELS OPEN

UNIT INFORMATION

FRAMING TYPE: Non-Thermal Perimeter Framing, Thermal G2 Hurricane Hook Rail Panels, 3" Stainless Steel Rollers

GLAZING SET UP: Opening for $\frac{3}{16}$ " Monolithic Glazing to 1" Insulated Glazing, Polycarbonate, or Solid Panel Infill


Decorative interior and exterior low profile grid option.

Motorized Panels Possible


Minimum Horizontal Panel Dimension 18". Smaller Panels may be available upon Engineering Approval

Designed and Manufactured in the U.S.A.

© 2017 Solar Innovations, Inc. - All Rights Reserved. These plans are the property of Solar Innovations, Inc. Any use or reproduction of these plans, in whole or in part, without the written permission of Solar Innovations, Inc. is forbidden.



© 2017 Solar Innovations, Inc. - All Rights Reserved. These plans are the property of Solar Innovations, Inc. Any use or reproduction of these plans, in whole or in part, without the written permission of Solar Innovations, Inc. is forbidden.



© 2017 Solar Innovations, Inc. - All Rights Reserved. These plans are the property of Solar Innovations, Inc. Any use or reproduction of these plans, in whole or in part, without the written permission of Solar Innovations, Inc. is forbidden.